

Aquaculture Innovation Workshop

Oct 14-15 2015

Shephardstown

Commercial application of denitrification in RAS

Ir. Victor Bierbooms

Viqon Water Solutions

The Netherlands



Project: ZON Aquafarming, Realization of market driven sustainable aquaculture production chain

Company: FISHION, job function RAS, R&D, design and realization

Period: 1996-2010


Location: southern part of the Netherlands, rural area

Fish: Tilapia

Farm size: 700 ton annual production


Production goal: 10.000 ton annual production

PROJECT STRUCTURE ZON



General RAS design

- low head design (total head loss 90 cm)
- energy 150 kW
- output 700 ton Tilapia 750 g



Set-up RAS



WATER BALANCE RESTRICTIONS

Expected water usage 700 ton tilapia farm 25 m³/hour




Well/discharge regulation, max. 10-15 m³/hour



Denitrification (manure as C-source)



Set-up DENOX system



Denitrification



SPECS SYSTEM RAS 700 ton Tilapia

RAS	
Recirculating flow (m3/hour)	6400
Average feeding level (kg/day)	2400
make up water (m3/day)	120
COD level (mg/l)	250
ortho-P	60
NO3 level (mg/l)	830

DENOX	
capacity (m3/hour)	20
Denitrification volume (m3)	135
Oxidation volume (m3)	90
Dry matter content active sludge (g/l)	6
NO3-N removal (g NO3-N/kg dm/hour)	2,3
NO3-N removal (mg NO3-N/l/hour)	14


WATER QUALITY

Influent denitrification	
volume spray water drumfilter (m3/day)	480
Dry matter content (g/l)	2
COD level (mg/l)	1700
Ortho-P (mg/l)	60
NO3 (mg/l)	830


Effluent denitrification	
Dry matter content (g/l)	0
COD level (mg/l)	250
Ortho-P (mg/l)	40
NO3 (mg/l)	380




NO₃ balance 700 Ton Tilapia farm with integrated DENOX system



NO DENOX, water balance costs Euro 0,23 Euro/kg production (maritime climate)



DENOX, water balance costs 0,17 Euro/kg production (maritime climate)




Water quality balance 700 Ton Tilapia farm after 2 years of production using denox system

Year	2007	2008	2009
Feeding level (kg/day)	1200	2400	2400
pH	8	5,8	5,9
NH ₄ (mg/l)	1,6	2	5
NO ₂ (mg/l)	0	0	1
NO ₃ (mg/l)	5	800	830
COD (mg/l)	24	160	250
ortho-PO ₄ (mg/l)	5	50	60
salinity (%)	0,05	0,08	0,19
alkalinity °d	6	0,3	0,5
Fe ²⁺ (mg/l)	0,02	1,3	1,6



Growth curve Tilapia

-Farm producing on fastest growth curve



Cost price comparison of 700 ton Tilapia RAS production unit with/without denox

	NO DENOX	DENOX
Cost price Tilapia (Euro/kg)	€ 2,34	€ 2,27
juveniles	€ 0,05	€ 0,05
feed	€ 0,90	€ 0,90
water intake/discharge/sludge	€ 0,14	€ 0,08
heating	€ 0,09	€ 0,01
electricity	€ 0,19	€ 0,21
labour	€ 0,14	€ 0,15
other	€ 0,10	€ 0,11
insurance	€ 0,10	€ 0,10
finance	€ 0,63	€ 0,66



Findings ZON aquafarming project

- 1) application of manure based denitrification in large scale Tilapia farming is feasible
- 2) denitrification reduces sludge volume with 30-35%
- 2) water usage of 40-50 l/kg feed is possible for efficient Tilapia production
- 3) no effect of denitrification on fish quality/flavor and growth
- 4) Ortho Phosphate level > 150 mg/l gives soap like flavor to fish
- 5) dissolved air flotation unit removes COD and PO_4 efficiently and makes the quality of denitrification effluent more stable
- 6) achieved manure based denitrification rate 2,3 g $\text{NO}_3\text{-N/g DM/hour}$ or 14 mg $\text{NO}_3\text{-N/l/hour}$
- 7) membrane flow filtration reduces flocculant use with 70-80% compared to traditional technique
- 8) denitrification can reduce water usage in RAS with 80-90%
- 9) feasibility denitrification depends a lot on local conditions



Latest developments


1) Application DENOX system in 300 ton eel farm as end of pipe solution

- increase $\text{NO}_3\text{-N}$ removal rate by discontinuous mixing (induce hydrolysis)
- optimized polymer use on DAF in combination with FeCl_3
- 99% NO_3 removal, 95% COD removal, process more difficult to control




Result

Effect on water discharge quality



2) Application in RAS biofloc shrimp production units (replacement sequence batch reactor)

- better and easier biofloc control
- easier management compared to SBR technique (no influence by sedimentation characteristics)
- smaller footprint
- simple set-up, DAF unit not required because of biofloc technique in production



3) application in industrial water treatment

- replacement of discontinuous SBR
- membrane flow filter used as sludge/water separation, replacing settling tanks, belt filters and DAF units



Questions?

Viqon Water Solutions
The Netherlands
www.viqon.com

